

66/90/80



UTILITY PATENT APPLICATION TRANSMITTAL <small>(Only for new nonprovisional applications under 37 CFR 1.53(b))</small>		Attorney Docket No. 1137-786A		Total Pages	
		First Named Inventor or Application Identifier			
		Masaki KINOSHITA			
		Express Mail Label No.			

525 U.S. PTO
09/369335
08/06/99

<p style="text-align: center;">APPLICATION ELEMENTS</p> <p>See MPEP chapter 600 concerning utility patent application contents.</p> <ol style="list-style-type: none"> 1. <input checked="" type="checkbox"/> Fee Transmittal Form <i>(Submit an original, and a duplicate for fee processing)</i> 2. <input checked="" type="checkbox"/> Specification Total pages [19] <i>(preferred arrangement set forth below)</i> <ul style="list-style-type: none"> - Descriptive title of the invention - Cross references to Related Applications - Statement Regarding Fed sponsored R&D - Reference to Microfiche Appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings - Detailed Description - Claims - Abstract of the Disclosure 3. <input checked="" type="checkbox"/> Drawing(s) (35 USC 113) (Total Sheets) [7] 4. <input checked="" type="checkbox"/> Oath or Declaration (Total Pages) [2] <ol style="list-style-type: none"> a. <input checked="" type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d)) <i>(for continuation/divisional with Box 17 completed)</i> <p style="text-align: center;">[Note Box 5 below]</p> <p><input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b)</p> 5. <input type="checkbox"/> Incorporation by Reference (useable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein. 	<p>ADDRESS TO: Assistant Commissioner of Patents Box Patent Application Washington, D.C. 20231</p> <ol style="list-style-type: none"> 6. <input type="checkbox"/> Microfiche Computer Program (Appendix) 7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) <ol style="list-style-type: none"> a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy) c. <input type="checkbox"/> Statement verifying identity of above copies <p style="text-align: center;">ACCOMPANYING APPLICATION PARTS</p> <ol style="list-style-type: none"> 8. <input checked="" type="checkbox"/> Assignment Papers (cover sheet & document(s)) 9. <input type="checkbox"/> 37 CFR 3.73(b) Statement <i>(when there is an assignee)</i> <ul style="list-style-type: none"> <input type="checkbox"/> Power of Attorney 10. <input type="checkbox"/> English Translation Document <i>(if applicable)</i> 11. <input type="checkbox"/> Information Disclosure Statement /PTO 1449 <ul style="list-style-type: none"> <input type="checkbox"/> Copies of IDS Citations 12. <input type="checkbox"/> Preliminary Amendment 13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) <i>(Should be specifically itemized)</i> 14. <input type="checkbox"/> Small Entity Statement(s) <ul style="list-style-type: none"> <input type="checkbox"/> Statement Filed in prior application, Status still proper and desired 15. <input checked="" type="checkbox"/> Certified Copy of Priority Document(s). <i>(if foreign priority is claimed)</i> 16. <input type="checkbox"/> Other:
---	--

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.:

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label or ☒ Correspondence address below
(Insert Customer No. or Attach bar code label here)

Name	Vincent M. DeLuca, Reg. No. 32,408				
Address	Rothwell, Figg, Ernst & Kurz Suite 701-East, 555 13th Street, N.W.				
City	Washington	State	D.C.	Zip Code	20004
Country	U.S.A.	Telephone	202-783-6040	Fax	202-783-6031

TITLE OF THE INVENTION

MOBILE TELEPHONE TERMINAL WITH IMPROVED UTILITY

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention generally relates to portable telephone terminals and, more particularly, to a portable telephone terminal having an answering function for switching between
10 answer messages in accordance with a caller number and the time, and also to a terminal operable by a remote telephone set using caller number authentication.

15 2. Description of the Related Art

Japanese Laid-Open Patent Application No. 10-66145 discloses a mobile communication terminal having an answering function for switching between answer messages depending on a caller number. A
20 call signal incoming at a called terminal from a calling terminal includes a caller number and control information for controlling the called terminal. The called terminal controls an answering mode and switches between answer
25 messages based on the caller number and the control information. Answer messages for individual expected callers are registered in the called terminal and retrieved according to the flowchart of Fig. 7. Each answer message has
30 associated therewith a message identification

number.

Referring to Fig. 7, when it is determined in step ST1001 that there is an incoming call, a determination is made in step 5 ST1002 as to whether the automatic answering mode is activated. When the answering mode is activated, a determination is made in step ST1003 as to whether a calling number is identified. If the calling number is identified, a determination 10 is then made in step ST1005 as to whether the calling number is registered in a directory. If the calling number is registered, a determination is made in step ST1006 as to whether the forced answering mode is on. If it is determined that 15 the forced answering mode is turned on, a determination is made in step ST1007 as to whether a predetermined answer message is to be used to automatically respond to the particular caller. If an affirmative answer is yielded in step ST1007, 20 the answer message for that caller is used for response in step ST1008. If a negative answer is yielded in steps ST1003, ST1005, ST1006 and ST1007, a default answer message is used for response to that caller in step ST1004.

25 If it is determined in step ST1002 that the answering mode is not activated, similar steps (ST1011, ST1012 and ST1009) are executed. When it is determined in step ST1009 that the forced answering mode is not turned on, a normal voice 30 call proceeds in step ST1010.

Japanese Laid-Open Patent Application No. 10-126495 and Japanese Laid-Open Patent Application No. 9-182158 disclose a portable telephone set provided with a capability whereby the portable telephone set, if lost, can be remotely operated by another telephone set so that a dialing operation using the lost portable telephone set is prohibited. Japanese Laid-Open Patent Application No. 10-126495 also discloses a portable telephone set configurable, if lost, for a fixed call destination by feeding a remote operation signal to the lost portable telephone set. Operations related to the memory are prohibited so that the leak of personal information and the illegal use of the portable telephone set are prevented. Japanese Laid-Open Patent Application No. 9-182158 discloses a system wherein a lock preventing an illegal use of a lost portable telephone set is registered in a base station using another telephone set so that call origination by an illegal user is prevented.

A rapidly increasing number of portable telephone sets is being used because of the convenience it provides in enabling communication not bounded by time and place constraints. When a user is not able to answer a call, the answering function is utilized. The related-art mobile communication terminal disclosed in Japanese Laid-Open Patent Application No. 10-66145 is provided with an answering function for switching between

answer messages depending on the caller number.
However, related-art mobile communication
terminals are not capable of switching between
answer messages for a particular caller in
5 accordance with the time that a call is received.

A user of a portable telephone set may
want to answer a call from a particular caller but
does not want to answer a call from the others.
The answering function that meets such a
10 requirement should be provided with a forced alert
function for alerting a user of a call from a
registered caller even when the answering mode is
activated.

Another problem with the portable
15 telephone system according to the related art is
that an input of a password is required when a
user calls a lost portable telephone set and
remotely sets up a locked dialing option in the
lost telephone set. When the user has forgotten
20 the password, the locked dialing option cannot be
set up when necessary.

SUMMARY OF THE INVENTION

Accordingly, an object of the present
25 invention is to provide a portable telephone set
in which the aforementioned problems are
eliminated.

Another and more specific object of the
present invention is to provide a mobile
30 communication terminal such as a portable

telephone set provided with an answering function that enables switching between answer messages in accordance with the time of calling.

Still another object of the present invention is to provide a portable telephone set in which a remote operation not requiring an input of a password is enabled by specifying terminal numbers (caller numbers) authorized to perform a remote operation for a locked dialing option or a voice mail option.

The aforementioned objects can be achieved by a mobile communication terminal comprising: timer means for detecting the time when a call incoming signal including a caller number is received from an originating terminal; caller number storage means for storing control codes in relation to expected caller numbers, the control codes being used to switch between different modes of operation of the mobile communication terminal; answer message storage means for storing messages to be returned to a caller; and answer message selecting means referring to said caller number storage means so as to determine whether the caller number included in the incoming call signal is registered in said caller number storage means, reading from said caller number storage means the control code associated with the caller number, and selecting an answer message stored in said answer message storage means based on the caller number, the

control code and the time of call detected by said timer means.

5 The caller number storage means may store caller numbers, caller names corresponding to the caller numbers and time-dependent switching codes in relation to each other, the time-dependent control codes designating callers for whom answer messages are switched depending on a time zone in which the call is made.

10 The caller number storage means may store caller numbers, caller names corresponding to the caller numbers and forced alert codes in relation to each other, the forced alert code designating callers triggering a forced alert
15 option for alerting a user of the mobile communication terminal of an incoming call even when an answering mode is activated.

The caller number storage means may store caller numbers, caller names corresponding
20 to the caller numbers and locked dialing codes in relation to each other, the locked dialing codes designating callers authorized to set up a locked dialing option in the mobile communication terminal from a calling terminal.

25 The caller number storage means may store caller numbers, caller names corresponding to the caller numbers and voice mail codes in relation to each other, the voice mail codes designating callers authorized to set up a voice
30 mail option in the mobile communication terminal

from a calling terminal.

According to the invention, mobile communication terminal is provided with an answering function capable of selecting an answer message in accordance with the caller number included in an incoming call signal and switching between answer messages depending on the time of call. Since it is possible to prepare a variety of answer messages suitable for individual expected callers, the answering function is enhanced.

The mobile communication terminal according to the invention is provided with the capability of alerting the user if a call is received from a designated caller even when the answering mode is activated, by recognizing the caller prior to an off-hook operation based on the caller number included in the incoming call signal. Therefore, it is possible to distinguish between callers requiring an answer and callers not requiring an answer.

In further accordance with the invention, when the caller number matches the registered number assigned a remote operation code, the caller is authorized to perform a remote operation such as setting up of a locked dialing option or a voice mail option. With this, it is possible to perform a remote operation without a password by calling from a registered terminal.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and further features of the present invention will be apparent from the following detailed description when read in
5 conjunction with the accompanying drawings, in which:

Fig. 1 is a block diagram showing the construction of a mobile communication terminal according to a first embodiment;

10 Fig. 2 is a diagram showing a call setting message;

Fig. 3 is a flowchart for the control of the answering function;

15 Fig. 4 shows a caller number registration table;

Fig. 5 is flowchart showing how a remote operation in a mobile communication terminal is controlled according to a second embodiment of the present invention;

20 Fig. 6 is a flowchart showing how a remote operation in a mobile communication terminal is controlled according to a third embodiment of the present invention; and

25 Fig. 7 is a flowchart showing how an answering function of a mobile communication terminal is controlled according to the related art.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

30 Embodiment 1

Fig. 1 is a block diagram showing the construction of a mobile communication terminal according to the first embodiment. Fig. 2 is a diagram showing a call setting message. Fig. 3 is a flowchart for the control of the answering function. Fig. 4 shows a caller number registration table.

The mobile communication terminal according to the first embodiment comprises an antenna for transmitting and receiving a modulated radio wave, a frequency converter (RF/IF unit) 2 for converting the frequency of the modulated radio wave, a modulating/demodulating unit 3 for modulating a carrier wave in accordance with a base band signal and for demodulating the modulated radio wave received via the antenna 1 to retrieve the base band signal. There are further provided a digital signal processing circuit 4 for subjecting the base band signal to TDMA signal processing, a speech signal processing circuit 5 for processing the base band signal, a controller 6, a time monitor unit 7 that includes a timer circuit, a memory 8, a keyboard 9, a speaker 10, a microphone 11 and a remote operation controller 12.

The memory 8 provides means for storing caller numbers and constitutes an answer message selecting means. In the memory 8, caller numbers, caller names, control codes (time-dependent switching codes, forced alert codes, message numbers selected in time zone 1 and in time zone

5

10

20

25

30

in a wait state in step ST301. A call is received in step ST302. After a predetermined period of time elapses (ST303), the terminal responds to call incoming (ST304). The terminal refers to the caller number registration table shown in Fig. 4 (ST305). If it is determined that the caller ID retrieved from the call setting message is registered in the caller number registration table (ST306), a determination is made as to whether the forced alert is set (ST307). If the forced alert is set, a call can proceed (ST308). When the call is terminated (ST309), the mobile communication terminal is returned to a wait state (ST310).

If it is determined that the caller ID retrieved from the call setting message is not registered in the caller number registration table (ST306), a preset message is sent to the network (ST317). When the preset message has been sent, the caller is allowed to leave a message (ST314). Control is then turned to step ST309.

If the originating ID is registered in the caller number registration table but the forced alert is not set, a message to be sent to the caller is selected in steps subsequent to ST311 depending on the time of call and the identity of the caller. In step ST311, the caller number registration table is examined so as to determine if time-dependent switching is set up for the caller. If it is determined that time-dependent switching is set up for the caller, the

time of call is detected by a timer circuit included in the time monitor unit shown in Fig. 1 (ST312). If the time of call from the caller is included in a first time zone, an answer message
5 designated for the caller and the first time zone is selected (ST313). Subsequently, the caller can record a message (ST314).

If it is not determined that the time of call from the caller is not included in the first
10 time zone, an answer message designated for the caller and a second time zone is selected (ST315). Subsequently, a message from the caller is recorded (ST314). If the call is from a caller for which time-dependent switching is not set up,
15 a predetermined message designated for the caller is selected and sent to the network (ST316). Subsequently, a message from the caller is recorded (ST314). Control is then turned to step ST309.

20 As has been described, the mobile communication terminal according to the first embodiment is provided with the capability of selecting an answer message depending on the caller and the forced alert capability for
25 alerting the user of the terminal when there is a call from a designated caller. Further, the answer message selecting capability is controlled in accordance with the time. Accordingly, the user of the terminal can properly set up the
30 terminal for expected callers.

Embodiment 2

Fig. 5 is a flowchart showing how a remote operation function of a mobile communication terminal is controlled according to the second embodiment. It is assumed that a portable telephone set (hereinafter, simply referred to as a terminal) is in a wait state (ST501). When a call arrives at the terminal (ST502), a determination is made as to whether the caller ID retrieved from the call setting message is registered in the caller number registration table and whether the caller is authorized to perform a remote operation (ST503). If it is determined that the caller is registered and authorized to perform a remote operation, after a predetermined period of time elapses (ST504), the terminal responds to the call (ST505).

When the caller inputs a number for setting up the locked dialing option (ST506), the terminal verifies the input number (ST507). If the input number is verified, the locked dialing option is set up (ST508). When the locked dialing option has been set up, the call is terminated (ST509), whereupon the terminal is placed in a wait state. When the number input for the locked dialing option is not verified, the number of times that the verification fails is counted (ST511). When the number of times exceeds a predetermined count, control is returned to step

ST506.

As has been described, the mobile communication terminal according to the second embodiment does not require an input of a password. Therefore, the user can set up a locked dialing option whenever necessary. By configuring the telephone set at home as the only authorized terminal, it is possible to prevent strangers from setting up the locked dialing option.

Embodiment 3

Fig. 6 is a flowchart for controlling the voice mail function of a mobile communication terminal according to the third embodiment. It is assumed that a portable telephone set (hereinafter, simply referred to as a terminal) is in a wait state in step ST601. When a call arrives at the terminal (ST602), a determination is made as to whether the caller ID retrieved from the call setting message is registered in the caller number registration table and whether the caller is authorized to perform a remote operation (ST603). If it is determined that the caller is registered and authorized to perform a remote operation, after a predetermined period of time elapses (ST604), the terminal responds to the call (ST605).

When the caller inputs a number for setting up a voice mail option (ST606), the input number is verified (ST607). If the input number is verified, the voice mail option is set up

(ST608). When the voice mail option has been set up, the call is terminated (ST609) so that the terminal is placed in a wait state (ST610). If the input number is not verified, the number of
5 times that the verification fails is counted (ST611). If the number of times exceeds a predetermined count (ST612), control is turned to step ST606.

As has been described, the mobile
10 communication terminal according to the third embodiment does not require an input of a password to set up a voice mail option remotely. Thus, even when the user has forgot the password, the user can still set up a voice mail option.

15 The present invention is not limited to the above-described embodiments and variations and modifications may be made without departing from the scope of the present invention.

WHAT IS CLAIMED IS:

5

1. A mobile communication terminal
comprising:

timer means for detecting the time when
a call incoming signal including a caller number
10 is received from an originating terminal;

caller number storage means for storing
control codes in relation to expected caller
numbers, the control codes being used to switch
between different modes of operation of the mobile
15 communication terminal;

answer message storage means for storing
messages to be returned to a caller; and

answer message selecting means referring
to said caller number storage means so as to
20 determine whether the caller number included in
the incoming call signal is registered in said
caller number storage means, reading from said
caller number storage means the control code
associated with the caller number, and selecting
25 an answer message stored in said answer message
storage means based on the caller number, the
control code and the time of call detected by said
timer means.

30

2. The mobile communication terminal according to claim 1, wherein said caller number storage means stores caller numbers, caller names corresponding to the caller numbers and time-
5 dependent switching codes in relation to each other, the time-dependent control codes designating callers for whom answer messages are switched depending on a time zone in which the call is made.

10

3. The mobile communication terminal
15 according to claim 1, wherein said caller number storage means stores caller numbers, caller names corresponding to the caller numbers and forced alert codes in relation to each other, the forced alert code designating callers triggering a forced
20 alert option for alerting a user of the mobile communication terminal of an incoming call even when an answering mode is activated.

25

4. The mobile communication terminal according to claim 1, wherein said caller number storage means stores caller numbers, caller names
30 corresponding to the caller numbers and locked

dialing codes in relation to each other, the
locked dialing codes designating callers
authorized to set up a locked dialing option in
the mobile communication terminal from a calling
5 terminal.

10 5. The mobile communication terminal
according to claim 1, wherein said caller number
storage means stores caller numbers, caller names
corresponding to the caller numbers and voice mail
codes in relation to each other, the voice mail
15 codes designating callers authorized to set up a
voice mail option in the mobile communication
terminal from a calling terminal.

669080" 5E69E60

ABSTRACT OF THE DISCLOSURE

A mobile communication terminal includes a timer for detecting the time of an incoming call, a caller number registration table for storing caller numbers, answer message ID numbers and time-dependent switching codes in relation to each other, the time-dependent control codes designating callers for whom answer messages are switched depending on a time zone in which the call is made. There is thus provided a capability of selecting an answer message for a caller based on the caller number included in the incoming call signal and switching between answer messages based on the time of call incoming detected by the timer.

669000-56660

FIG.1




FIG.2

CALL SETTING MESSAGE




FIG.3






FIG.4

NAME	PHONE NUMBER	ANSWER MESSAGE 1 (TIME ZONE 1)	ANSWER MESSAGE 2 (TIME ZONE 2)	TIME-DEPENDENT SWITCHING	FORCED ALART
ICHIRO TOYOTA	020-123-4567	1	2	1	1
JIRO SUZUKI	020-234-5678	2			
SABURO MATSUDA	020-345-6789	3	2	1	
SHIRO HONDA	020-456-7890	1	3	1	
TARO MITSUBISHI	020-567-8901	3			1



ANSWER MESSAGE 1: THIS IS XX. I CANNOT TAKE THE PHONE NOW BECAUSE OF THE MEETING.
PLEASE LEAVE A MASSAGE SO I CAN RETURN A CALL.
ANSWER MESSAGE 2: THIS IS XX. I HAVE LEFT THE OFFICE.
PLEASE LEAVE A MESSAGE SO I CAN RETURN A CALL TOMORROW.
ANSWER MESSAGE 3: THIS IS XX. I CANNOT TAKE THE PHONE NOW.
PLEASE LEAVE A MESSAGE.

FIG.5



WHEN THE LOCKED DIALING OPTION IS SET UP, THE TERMINAL CAN ONLY ANSWER A CALL. OPERATIONS SUCH AS DISPLAY OF A DIRECTORY AND DISPLAY OF A MENU ARE DISABLED.

FIG.6





FIG. 7(PRIOR ART)



Attorney Docket No. _____

**Declaration and Power of Attorney
For Patent Application
(Sole/Joint)**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought, on the invention entitled "MOBILE TELEPHONE TERMINAL WITH IMPROVED UTILITY"

_____ the specification of which (Check One)

☒ is attached hereto.

_____ was filed on _____ as

☐ Application Serial No. _____

☐ International Application No. PCT/_____

and was amended on _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

			Priority Claimed	
<u>10-277652</u>	<u>Japan</u>	<u>30/September/1998</u>	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)		
_____	_____	_____	Yes: <input type="checkbox"/>	No: <input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)		
_____	_____	_____	Yes: <input type="checkbox"/>	No: <input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)		

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose

material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

(Application Serial No.)	(Filing Date)	(Status)
(Application Serial No.)	(Filing Date)	(Status)

I or we hereby appoint the following attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and request that all correspondence about the application be addressed to ROTHWELL, FIGG, ERNST & KURZ, P.C., 555 13th Street, N.W., Washington, D.C 20004

G. Franklin Rothwell, Reg. No. 18,125
E. Anthony Figg, Reg. No. 27,195
Barbara G. Ernst, Reg. No. 30,377
George R. Repper, Reg. No. 31,414
Lawrence G. Norris, Reg. No. 18,034
Bart G. Newland, Reg. No. 31,282
Vincent M. DeLuca, Reg. No. 32,408
Joseph A. Hynds, Reg. No. 34,627

Michael G. Sullivan, Reg. No. 35,377
Jeffrey B. McIntyre, Reg. No. 36,867
Robert J. Jondle, Reg. No. 33,915
Moon Soo Lee, Reg. No. 37,377
Kenneth M. Fagin, Reg. No. 37,615
Stephen B. Parker, Reg. No. 36,631

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full Name of Sole or First Inventor	Inventor's Signature	Date
Masaki KINOSHITA	木下真樹	July 27, 1999
Residence	Tokyo, Japan	Citizenship
		Japanese
Post Office Address	c/o MITSUBISHI DENKI KABUSHIKI KAISHA, 2-3, Marunouchi 2-chome, Chiyoda-ku, Tokyo 100-8310 Japan	
Full Name of Second Joint Inventor, if any	Inventor's Signature	Date
Residence		Citizenship
Post Office Address		
Full Name of Third Joint Inventor, if any	Inventor's Signature	Date
Residence		Citizenship
Post Office Address		
Full Name of Fourth Joint Inventor, if any	Inventor's Signature	Date
Residence		Citizenship
Post Office Address		